



Beacons Series „P“

LED Steady/Flashing/Multi Strobe Beacons
LED Multi Colour Beacons
Xenon Strobe Beacons



Ø 75 mm

Model Overview	Ø 75 mm high lens	Ø 75 mm low lens
LED steady/flashing beacon	PCH	PCL
LED multi strobe beacon	PFH	PFL
LED multi colour beacon red-yellow-green	PMH	---
Xenon strobe beacon	PXH	PXL

Features

- ▶ Ø 75 mm large compact and brilliant beacon range
- ▶ High ingress protection
- ▶ Prewired with 1 m cable with PUR-jacket, open ends, ready to use
- ▶ Premounted stainless fixation screws
- ▶ Customized cable lengths/specifications possible
- ▶ Complete offering of beacons with modern LED technique (long lifetime, low current consumption, vibration-proof)
- ▶ LED multi strobe beacon with 2 LED strobe patterns (LED 6-times strobe/LED multi strobe), externally switchable
- ▶ LED multi colour beacons red-green with clear lens
- ▶ Models with high and low lens
- ▶ Xenon strobe models with voltage range 10-100 V AC/DC
- ▶ Mounting options horizontal (standard), vertical and pole mounting (accessory)
- ▶ Lens and base components made of high impact resistant polycarbonate
- ▶ Excellent price/performance ratio
- ▶ For use in industrial/process/general applications
- ▶ Fit for plc applications (leakage, inrush current)

Mounting options


- ▶ **Horizontal mounting**
(standard)




- ▶ **Vertical mounting**
Accessory: plastic bracket (PVW)



- ▶ **Pole mounting**
Accessory: Pole mounting (PMR)





Order data

Type	Denomination	Light source	Nominal voltage (V)	Voltage range (V)	Nominal current (A)*	Order No. Housing black	Price
Models with high lens							
PCH	LED steady/flashing beacon	integrated LEDs	24 V AC/DC	+/- 10 %	0,240	860 50C 405	
			110/120 V AC		0,095	860 50C 310	
			230/240 V AC		0,095	860 50C 313	
PFH	LED multi strobe beacon	integrated LEDs	24 V AC/DC	+/- 10 %	max. 0,360	860 51C 405	
			110/120 V AC		0,095	860 51C 310	
			230/240 V AC		0,095	860 51C 313	
PMH**	LED multi colour beacon red-yellow-green	integrated LEDs	24 V AC/DC	+/- 10 %	---	860 550 405	
			110/120 V AC		---	860 550 310	
			230/240 V AC		---	860 550 313	
PXH	Xenon strobe beacon	5 J xenon tube	24 V AC/DC	+/- 10 %	0,450	860 52C 405	
			110/120 V AC		0,100	860 52C 310	
			230/240 V AC		0,050	860 52C 313	
			10-100 V AC/DC	10-100 V DC	0,500	860 52C 410	
				10-70 V AC	0,500		
Models with low lens							
PCL	LED steady/flashing beacon	integrated LEDs	24 V AC/DC	+/- 10 %	0,060	861 50C 405	
			110/120 V AC		0,030	861 50C 310	
			230/240 V AC		0,031	861 50C 313	
PFL	LED multi strobe beacon	integrated LEDs	24 V AC/DC	+/- 10 %	max. 0,155	861 51C 405	
			110/120 V AC		0,045	861 51C 310	
			230/240 V AC		0,045	861 51C 313	
PXL	Xenon strobe beacon	2 J xenon tube	24 V AC/DC	+/- 10 %	0,200	861 52C 405	
			110/120 V AC		0,050	861 52C 310	
			230/240 V AC		0,025	861 52C 313	
			10-100 V AC/DC	10-100 V DC	0,200	861 52C 410	
				10-70 V AC	0,200		

* provisional value ** scheduled for end of 2013

Accessories

Type	Denomination	Order No.	Price
PVW	Bracket for vertical mounting	860 600 900	
PMR	Pole mounting, 100 mm aluminium tube with plastic foot	860 702 900	
	Pole mounting, 250 mm aluminium tube with plastic foot	860 703 900	

DISTRIBUTOR

GEUKEN B.V.

Wattstraat 15a
2723 RA Zoetermeer / NETHERLANDS
Tel. +31 (0)79 361 60 70
Fax +31 (0)79 361 40 90
info@geuken.nl
www.geuken.nl

HEADQUARTERS

**J.AUER – FABRIK ELEKTRISCHER
MASCHINEN Ges.m.b.H.**

Perfektastraße 102
1230 Vienna / AUSTRIA
Tel. +43 (0)1 813 82 20
Fax +43 (0)1 815 99 51
office@auer-signal.com
www.auer-signal.com

SALES GERMANY

J.AUER – SIGNALGERÄTE GmbH

Sperberweg 11
41468 Neuss / GERMANY
Tel. +49 (0)2131 29 86 86-0
Fax +49 (0)2131 29 86 86-6
info@auer-signal.de
www.auer-signal.com